

Ohio EPA

Backflow Prevention and Cross-Connection Control 2019

Protecting our Public Water System



Division of Drinking & Ground Waters
122 South Front St., PO Box 1049
Columbus, Ohio 43216-1049
(614) 644-2752
www.epa.state.oh.us



City of Cortland
Attn: Backflow Coordinator
400 North High Street
Cortland, OH 44410
330-637-3916
info@cityofcortland.org

What is a cross-connection?

A cross connection is any physical connection created between a possible source of contamination and any drinking water system piping.

What is backflow?

Backflow means the flow of water through a cross-connection from a possible source of contamination back into the drinking water system.

Why does backflow occur?

Backflow occurs when a cross-connection is created and a pressure reversal, either as backsiphonage or backpressure, occurs in the water supply piping or within the household plumbing.

Why should you be concerned?

- ALL cross-connections pose a potential health risk.
- Chemical burns, fires, explosives, poisonings, illness and death have all been caused by backflow through cross-connections.
- Backflow can be a health hazard for your family or other consumers if contaminated water enters your water supply plumbing system and is used for drinking, cooking, or bathing.
- Backflow occurs more often than you think.
- Cross-connections with water supply plumbing or public drinking water piping systems are prohibited by law.
- Protecting the public water system from backflow contamination is the law.
- YOU are responsible for protecting your water supply plumbing from backflow that may contaminate your drinking water and the drinking water of others. This includes complying with the plumbing code and not creating cross-connections.

What must be done to protect the public water system?

The water supplier is required to determine potential and actual hazards. If a hazard exists at a customer's service connection to the public water system, the customer will be required to install and maintain an appropriate backflow prevention device* at the meter and/or at the source of the hazard.

What causes backsiphonage?

Backsiphonage occurs when there is a loss of pressure in a piping system. This can occur if the water supply pressure is lost or falls to below the pressure of the source of contamination. This

condition, which is similar to drinking from a glass with a straw, allows liquids to be siphoned back into the distribution system.

What causes backpressure?

Backpressure occurs when an opposing pressure is applied against the public water system's supply pressure and the higher pressure overcomes the public water system's pressure. This condition allows undesirable gases or liquids from another system to enter into the drinking water supply. Any pumping system (such as a well pump) or pressurized system (such as steam or hot water boilers) can exert backpressure when cross-connected with the public water system.

What are some common backflow hazards that threaten the homeowner and other consumers?

- Hose connections to chemical solution aspirators to feed lawn and shrub herbicides, pesticides or fertilizers. Lawn irrigation systems.
- Chemically -treated heating systems
- Hose connections to a water outlet or laundry tub.
- Swimming pools, hot tubs, spas.
- Private and/or non-potable water supplies located on the property.
- Water-operated sump drain devices.
- Feed lots/livestock holding areas or barnyards fed through pipes or hoses from your water supply plumbing.

What are examples of cross-connection and backflow scenarios?

- Soapy water or other cleaning compounds backsiphoned into your water supply system through a faucet or hose submerged in a bucket or laundry basin.
- A hose submerged in a swimming pool or at a dock that creates a pathway for pool/lake water to enter your water supply plumbing.
- Fertilizers/pesticides backsiphoned into your water supply plumbing through a garden hose attached to a fertilizer pesticide sprayer.
- Chemicals/pesticides and animal feces drawn into your water supply plumbing from a lawn irrigation system with submerged nozzles.
- Bacteria/chemicals/additives present in a boiler system backsiphon into the water supply plumbing.
- A connection made between a private well supply and the water being supplied by a public water system through the water supply plumbing.

What can you do to prevent backflow situations in your home or business?

- Be aware of and eliminate cross-connections.
- Maintain air gaps. Do not submerge hoses or place them where they could become submerged.
- Use hose bib vacuum breakers on fixtures (hose connections in the basement, laundry room and outside).
- Install approved, test-able backflow prevention devices on lawn irrigation systems.
- Do not create a connection between an auxiliary water system (well, cistern, body of water) and the water supply plumbing

Who is responsible?

In Ohio, the responsibility for preventing backflow is divided. In general, state and local plumbing inspectors have authority over plumbing systems within buildings while Ohio EPA and water suppliers regulate protection of the distribution system at each service connection. Water customers have the ultimate responsibility for properly maintaining their plumbing systems. It is the homeowner's or the customer's responsibility to ensure the cross-connections are not created and that any required backflow prevention devices are tested yearly and are in operable condition.

What is the law?

Ohio Administrative Code Chapter 3745-95 requires the public water supplier to protect the public water system from cross-connections and prevent backflow situations. The public water supplier must conduct cross-connection control inspections of their water customers' property to evaluate cross-connection hazards. Local ordinances or water department regulations also exist that must be followed in addition to state regulations.

If a customer is found to have a potential or actual cross-connection contamination hazard, the customer will be required to eliminate the hazard and/or install an appropriate backflow prevention device at the service connection and/or at the hazard.

*Check with the City of Cortland at 330-637-3011 or admin@cityofcortland.org for the appropriate backflow prevention device required before purchase or installation of the device.

Special Conditions

Auxiliary Water Systems

What is an auxiliary water system?

Any water system on or available to your property other than the public water system. Used water or water from wells, cisterns or open reservoirs that are equipped with pumps or other sources of pressure, including gravity, are examples.

What protection is required?

- The auxiliary water system must be completely separated from water supply plumbing served by a public water system; and
- An approved backflow prevention device must be installed at the service connection (where the public water system connects to the customer's plumbing system), OR
- The auxiliary water system must be eliminated.

Are there exceptions?

The water supplier may waive the requirement for a backflow prevention device at the service connection, at the discretion of the water supplier, if:

- All components of the auxiliary water system, including pumps, pressure tanks and piping, are removed from the premises, which is defined as all buildings, dwellings, structures or areas with water supply plumbing connected to the public water system; and
- The possibility of connecting the auxiliary water system to the water supply plumbing is determined by the water supplier to be extremely low; and
- No other hazards exist; and
- The customer enters into a contract with the water supplier.

The contract will require the customer:

- To understand the potential hazard of a cross-connection;
- To never create a cross-connection between the auxiliary water system and the public water system;
- To allow an inspector to survey his/her property for hazards as long as the contract is in effect; and
- To face loss of service and other penalties if the contract is violated.

The water supplier must perform an annual inspection of the customer's contract-regulated property to verify the

conditions have not change, which would warrant the installation of a backflow preventer. The water supplier must do everything reasonably possible to protect the water system from contamination.

Booster Pumps

What is the concern?

Booster pumps connected to plumbing systems or water mains can reduce the pressure in water mains causing backsiphonage conditions by reducing water mains. The following requirements are in place to help prevent backsiphonage:

- Booster pumps, not used for fire suppression, must be equipped with a low suction cut-off switch that is tested and certified every year;
- Alternatively, when a booster pump is necessary for one-, two- and three-family dwellings, it is preferred that the booster pump draw from a surge tank filled through and air gap; and
- Booster pumps, used in fire suppression system, must be equipped with either a low suction throttling valve on the discharge side or be equipped with a variable speed suction limiting control system. Low-pressure cut-off devices will suffice for fire pumps installed prior to August 8, 2008, until a significant modification is warranted, at which point the minimum pressure sustaining method must be updated. Each of these methods must be tested and certified each year.

Contacts

Need more information?

Questions concerning backflow prevention and cross connection control may be directed to your local water department at the number shown on the front of this brochure, to Ohio EPA's Division of Drinking and Ground Waters central office at (614) 644-3752, or to your local Ohio EPA district office at the following number :

Northeast District (330) 963-1200

Questions regarding internal plumbing in the home may be directed to Trumbull County Plumbing Inspector, the City of Cortland or the Ohio Department of Commerce, Plumbing Administrator at (614) 644-3153